

4CH POE NVR Kit(2M)



Key Features

- Compression Method: H.265/H.264
- Preview Resolution: 2M
- POE Plug and Play
- One Stop Solution Package
- Dimensions Package (L×W×H): 395*245*275(mm)

Technical Specifications

Model	FX-K202POE
Package	
NVR	1x NVR
Camera	4 xFX-IP202D
Cable	4x 20m CAT5e Cable
Mouse	1xUSB 2.0 Mouse
Adaptor	DC52V/1.25A
Hard Disk	No
Camera	
Image Sensor	1/2.9" CMOS Sensor
Resolution	2MP 1080P
S/N Ratio	≥52dB
Lens	3.6mm
Infrared LED	14μ x 18PCS
Infrared Distance	20M
POE	Internal POE, Support IEEE 802.3af
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog Mode	Support
BLC	Support
WDR	Support
Motion Detection	Support
Housing	Metal , IP66
Dimension	φ93 x 74(H) mm
NVR	
Main Processor	Hi3536D
Operating System	Embedded LINUX
Input	9CH (2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, etc)
Output	1 VGA, 1 HD
Motion Detection	9 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output
HD Output	Resolution: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Record Rate	PAL :5MP@9×25fp,4MP@9×25fp,3MP@9×25fp,1080P@9×25fp, 960P@9×25fp,720P@9×25fp, D1@9×25fp NTSC: 5MP@9×30fp,4MP@9×30fp,3MP@9×30fp,1080P@9×30fp, 960P@9×30fp, 720P@9×30fp, D1@9×30fp
Record Resolution	5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480)
Playback Decode Capability	4CH 1080P@20fps
Incoming Bandwidth	60MB
Storage	1 SATA Interface (Up to 8TB)
Power Supply	DC 52V/1250mA ≤6W (Without Hard Disk and POE)
Dimension(W×D×H)	260*215*43(mm)

>>Specifications are subject to change without prior notice