

4CH POE NVR Kit(2M)



CCTV



● Key Features

- Compression Method: H.265/H.264
- Preview Resolution: 2M
- POE Plug and Play
- One Stop Solution Package
- Dimensions Package (L×W×H): 395*245*275(mm)

● Technical Specifications

Model	FX-K402POE
Package	
NVR	1x NVR
Camera	2 xFX-IP202D, 2 xFX-IP202B
Cable	4x 20m CAT5e Cable
Mouse	1xUSB 2.0 Mouse
Adaptor	DC52V/1.25A
Hard Disk	No
Camera	
Image Sensor	1/2.9" CMOS Sensor
Resolution	2MP 1080P
S/N Ratio	≥52dB
Lens	3.6mm
Infrared LED	Dome: 14μ x 18PCS Bullet: 14μ x 20PCS
Infrared Distance	Dome: 20M Bullet: 25M
POE	Internal POE, Support IEEE 802.3af
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog Mode	Support
BLC	Support
WDR	Support
Motion Detection	Support
Housing	Metal , IP66
Dimension	Dome: φ93 x 74(H) mm Bullet: 157(W) x 70(H) x 66(D)mm
NVR	
Main Processor	Hi3536D
Operating System	Embedded LINUX
Input	9CH (2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, etc)
Output	1 VGA, 1 HD
Motion Detection	9 Channel, MD Zones: 396 (22 x 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output
HD Output	Resolution: 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
Record Rate	PAL :5MP@9x25fp,4MP@9x25fp,3MP@9x25fp,1080P@9x25fp, 960P@9x25fp,720P@9x25fp, D1@9x25fp NTSC: 5MP@9x30fp,4MP@9x30fp,3MP@9x30fp,1080P@9x30fp, 960P@9x30fp, 720P@9x30fp, D1@9x30fp
Record Resolution	5MP(2592x1944),4MP(2688x1520/2560x1440),3MP(2048x1536),1080P(1920x1080),960P(1280x960),720P(1280x720),D1 (720x576/720x480)
Playback Decode Capability	4CH 1080P@20fps
Incoming Bandwidth	60MB
Storage	1 SATA Interface (Up to 8TB)
Power Supply	DC 52V/1250mA ≤6W (Without Hard Disk and POE)
Dimension(WxDxH)	260*215*43(mm)

>>Specifications are subject to change without prior notice