

EM-201GDS

Resettable Emergency Door Release with symbol

Description:

The EM201GDS resettable door release is unlike the break glass unit. It offers the benefits & environmental advantages of a resettable operating element.

Key Features:

- Flexible manual call point, Comply with a requirement of EN54-11
- Fast and easy installation, Special tool operating test facility
- Unique 'Plug & Play' installation concept
- Simple maintenance Only one tool is needed for test and reset
- Choice of surface or flush mount, Marking options

Technical Specification:

- Operating voltage: 30 VDC
- Operating current: 2 A
- Withstood-voltage: 250 VAC
- Temperature range: -10 ~ 60 °C
- Humidity: 0 ~95% non-condensing
- Ingress protection rating: IP24D
- Mounting way: Wall mounting
- Terminal: Double pole
- Dimension: 87 mm x 87 mm x 52 mm



Kyodensha Technologies (M) Sdn Bhd (2057536-M) Information Communication Technologies (M) Sdn Bhd (640944-K-M) Digit Innovation Technologies (M) Sdn Bhd (646972-U)

No, 7 Jalan TPP 1/15, Taman Industri Puchong Batu 12, Jalan Puchong, 47100 Puchong Selangor, Malaysia

 TEL
 +603 8061 4589 +603 8061 3201

 FAX
 +603 8944 1715

 WEB
 www.elock2u.com

 EMAIL
 sales@elock2u.com