

Indoor Monitor

Performance configuration

- Video monitor
- Call manager
- Intercom unlocking
- Information service
- Can be used as a duplex extension
- Secondary confirmation doorbell interface
- Hands-free video intercom
- Elevator linkage control
- Comes with 2 zones
- Visitor photo message inquiry

Product parameters

Display: 4.3 inch color LCD screen

Resolution: 480X272

Mode of operation: button

Transmission method: digital transmission

Input power: 12-18V DC

Device power consumption: standby 10mA, maximum 250mA

Working temperature: -10 °C ~ 55 °C

Installation method: wall-mounted

Product size: 180×128×22mm

Product material: ABS

FX-R431-H



Performance configuration

- Video monitor
- Call manager
- Intercom unlocking
- Information service
- Can be used as a duplex extension
- Secondary confirmation doorbell interface
- Hands-free video intercom
- Elevator linkage control
- Comes with 2 zones
- Visitor photo message inquiry

Product parameters

Display: 4.3 inch color LCD screen

Resolution: 480X272

Mode of operation: button

Transmission method: digital transmission

Input power: 12-18V DC

Device power consumption: standby 10mA, maximum 250mA

Working temperature: -10 °C ~ 55 °C

Installation method: wall-mounted

Product size: 180×128×22mm

Product material: ABS

FX-R153-H

