

CC2.4Wi-Fi

Fingerprint Card Access

Password







HIGH SECURITY TIME ATTENDANCE & ACCESS CONTROL

www.zetekuae.com

New model FF1A is popular in the market with smart desgin, improved function that support, WIFI, access control, bell, battery, RFID, professional communication port, 1 × relay, NC, NO, push button, etc. Device with 2.8 inches color screen to be more humanized. Data managed via TCP/IP, WiFi, and USB host port for data upload/download to avoid the risk of accidental deletion. What's more, friendly software eTime with perfect setting of shifts, rules, employees, departments, etc.

- •World-class algorithm, high-speed and accurately identify fingerprint.
- •Fingerprint/Pin/Card authentication.
- •Suitable for the entrances and exits of office, factory, hotel, school, etc.
- •Large capacity, user capacity up to 3,000 & logs capacity up to 200,000. • Multiple shifts setting.
- •2.4 inches color screen 320x240 pixel.
- •TCP/IP + USB Flash Drive Download + USB Communication.

• Support door control / alarm function.

- •USB flash drive for offline data management.
- Multi-language: English, Arabic, French, Spanish, Portuguese, etc.
- Professional T&A software eTime.
- Easy wall-mounting.

• More helpful function like T9 input method, self-service inquiry, etc.

• Exact calculation of worked hours / overtime.

Technical Specification

| Model | FF1A |
|-----------------------------|---|
| Biometric measurement | Fingerprint |
| Fingerprint capacity | 3,000 |
| Log capacity | 200,000 |
| CPU | 320MHz |
| LCD display | 2.8" TFT color screen 320x240 pixel |
| Interface | TCP/IP, USB (host and slave), 1 × Relay |
| Language | English, Arabic, French, Korean, Spanish, Portuguese, etc |
| Attendance mode | Fingerprint or Password or Card or Fingerprint+Password |
| | or Card+Password or Fingerprint+Card+Password |
| Voice instruction | 16-bit Hi-Fi voice & sound indication |
| Verification time | < 0.5 second [1:N] |
| FRR (False Rejection Rate) | < 1% |
| FAR (False Acceptance Rate) | < 0.0001% |
| Power source | 5VDC/1A |
| Operating temperature | 0 - 45 Degree Celsius |
| Operating humidity | <90%RH |
| Dimensions (mm) | 160 x 61.5 x 141 |
| Weight (kg) | 0.33 |
| Quantity/Carton | 10 units |
| Gross weight/carton (kg) | 9.5 |

Fingerprint **Access Control**

Brand: Felix

Model: FF1A Software: eTime T&A





Optional Function

RF Card:13.56MHZ Mifare Backup Battery: 2-4 Hours for working





T9 Input




2.4 Inches TFT Color Screen




Optical Fingerprint Sensor






<u>Accessories</u>





<u>Interface</u>





>> Specifications are subject to change without prior notice.

www.zetekuae.com